

DWARSPROFIEL 40

H.Schaal : 1/100
V.Schaal : 1/100

Referentielijn 2.00 m

4.77	1.00	15.92
4.86	1.88	14.92
5.25	0.26	13.05
5.43	1.96	12.79
5.55	2.60	10.83
5.45	1.61	8.23
5.43	0.57	6.62
5.19	1.41	6.05
3.60	1.80	4.65
2.07	1.05	2.18
1.69	1.14	1.13
1.51	1.26	0.00
1.83	1.32	-1.26
1.95	0.74	-2.58
2.22	1.18	-3.32
3.35	3.06	-4.51
4.02	1.13	-7.57
4.13	0.89	-8.70
4.35	0.67	-9.59
5.40	0.79	-10.26
5.86	0.38	-11.05
5.77	0.89	-11.43
5.58	0.61	-12.32
5.53	0.92	-12.94
4.95	1.86	-13.86
4.43	1.63	-15.72
4.07	0.24	-17.35
3.90	0.00	-17.59
TERREINHOOGTE	(m)	
TUSSENAFSTAND	(m)	
GECEMULEERDE AFSTAND	(m)	

K40

HOUTEN PLANKEN


+3.59

+3.37

+1.51

K40

LENGTEPROFIEL Schaal 1/100



STROOMRICHTING