

DWARSPROFIELPLAN

Aangeduide kruinbreedtes zijn indicatief.

Opgemeten in: Februari 2020

Opgemeten volgens bestek: W/TOPO/2019/01

vaste bodem

slibbodem

oeverversterking

0.00

kruinbreedte (m)

as dwarsprofiel

haag

gebouw

STRAATNAAM

straatnaam

weide-afsluiting

afsluiting

BV

beginpunt verharding

BO

beginpunt Onverharde weg

beginpunt begroeiing

beginpunt Oeverversterking

beginpunt begroeiing

beginpunt Oeverversterking

Hoogstammige boom

Laagstammige boom

schanskorven

steenstorting

prefab elementen

beton

metselwerk in diverse materialen

erosiewerend weefsel

gefixeerde steenbestorting

houtmatten

A

andere

DP

damplanken

Bt

betuining

PB

palen bordage

DWARSPROFIEL DA20-1

Hsch 1/100
Lsch 1/100
Vvlak 10.00T.A.W.

The diagram shows a cross-section profile of a waterway. The top line represents the ground level (Hs), and the bottom line represents the water level (Ls). The water level is indicated by a blue line with a value of 5.73. The ground level is indicated by a red line with a value of 05144. The profile includes several trees, a wall, and a road. The table below provides the elevations and distances for each section.

HOOGTEPEIL	12.73	12.83	13.09	13.16	12.63	12.28	11.93	11.59	11.20	11.20	11.45	11.98	12.32	12.73	12.87	12.94	12.95	12.89	12.85	12.75
SLIB					12.28	12.17	11.90	11.72	11.72	11.72	11.83	11.98								
TUSSENAFSTAND	0.20	2.00	2.81	1.46	2.73	0.28	0.58	0.47	0.78	1.12	0.86	0.70	0.56	0.49	0.62	1.49	1.85	2.54	2.11	2.30
KUMULAFSTAND	-12.22	-10.22	-7.41	-5.96	-3.24	-2.95	-2.37	-1.90	-1.12	0.00	0.86	1.56	2.12	2.62	3.24	4.73	6.58	9.12	11.23	13.54