

O8313 Akker Heinewatergang

(VHAG: 2912)

KAPRIJKE

OPM_O8313_2020_Dwarsprofiel_DA20-3

DWARSPROFIELPLAN

Aangeduide kruinbreedtes zijn indicatief.

Opgemeten in: Maart 2020

Opgemeten volgens bestek: TO/2019-01

LEGENDE

vaste bodem

slibbodem

oeverversterking

kruinbreedte (m)

as dwarsprofiel

haag

gebouw

STRAATNAAM

straatnaam

weide-afsluiting

afsluiting

beginpunt verharding

beginpunt Onverharde weg

beginpunt begroeiing

beginpunt Oeverversterking

Hoogstammige boom

Laagstammige boom

schanskorven

steenstorting

prefab elementen

beton

mettselwerk in diverse materialen

erosiewerend weefsel

gefixeerde steenbestorting

houtmatten

andere

DP

damplanken

Bt

betuining

PB

palen bordage

DWARSPROFIEL DA20-3

Hsch 1/100
Lsch 1/100
Vvlak 2.00 T.A.W.

The diagram shows a cross-section profile with a cyan line for the ground surface and a green line for the water level. A red vertical line marks the centerline, labeled 'O8313'. A blue arrow indicates a width of 2.49 m. The profile is divided into sections with varying widths. Below the profile is a table with four rows: HOOGTEPEIL, SLIB, TUSSENAFSTAND, and KUMULAFSTAND. The HOOGTEPEIL row shows elevations from 4.64 to 4.52. The SLIB row shows values from 3.69 to 3.63. The TUSSENAFSTAND row shows distances from 5.41 to 2.15. The KUMULAFSTAND row shows cumulative distances from -14.59 to 14.65.

HOOGTEPEIL	4.64	4.68	4.66	4.67	4.62	4.55	4.53	4.27	3.69	3.42	3.63	4.46	4.55	4.55	4.61	4.59	4.56	4.52	
SLIB									3.69	3.47	3.63								
TUSSENAFSTAND	5.41	2.18	1.85	2.00	1.89	1.84	2.17	1.42	0.63	0.61	0.55	0.92	0.31	1.59	2.11	2.45	2.39	2.20	2.15
KUMULAFSTAND	-14.59	-12.41	-10.56	-8.56	-6.67	-4.83	-2.66	-1.23	-0.61	0.00	0.55	1.46	1.77	3.36	5.46	7.91	10.30	12.50	14.65