

Legende

vaste bodem

kunswerk

slibbodem

as dwarsprofiel

begin begroeiing

haag

boerand

bomenrij van loofbomen

bomenrij van naaldbomen

bomenrij van fruitbomen

duiker as

beton

metseelwerk

gebouw

bergplaats

kaalmuur

afsluiting algemeen

afsluiting beton + gladde draad

afsluiting beton + prikkeldraad

afsluiting hout + gladde draad

afsluiting hout + prikkeldraad

afsluiting betonpalen en -platen

muurtje metseelwerk

hout

metaal

The figure shows a cross-section profile of a ditch. The top line (cyan) represents the ground level (vaste bodem). The bottom line (black) represents the ditch bottom (slibbodem). The ditch is filled with concrete (beton) and has a metal (metaal) lining. The profile is divided into sections by vertical lines. A red vertical line marks the center of the ditch. The table below provides the measurements for each section.

PEIL VASTE BODEM	19.92	20.02	20.08	20.21	20.22	20.22	20.03	19.51	19.10	18.99	19.01	19.44	20.42	20.41	20.40	20.25	20.13	20.08	19.96
TUSSENAFSTAND VASTE BODEM	2.16	2.16	4.77	2.08	1.48	1.81	0.25	0.15	0.47	0.39	0.31	1.20	2.50	2.40	1.63	1.93	2.51	2.39	1.51
SAMENGESTELDE AFSTAND VASTE BODEM	12.92	15.08	17.24	22.01	24.09	25.57	27.38	27.63	27.79	28.25	28.65	28.96	30.16	32.67	35.06	36.70	38.63	41.14	43.53
PEIL SLIBBODEM							19.10	18.99	19.01										
TUSSENAFSTAND SLIBBODEM	27.79						0.47	0.39											
SAMENGESTELDE AFSTAND SLIBBODEM							27.79	28.25	28.65										

Gemeente Herent

B2105

Hoge Beek

VHAG: 6858

Locatie ataspunt (LB72):

X-coördinaat: 170127,4489 Y-coördinaat: 179231,6258

DWARSPROFIELPLAN

Ataspunt - 024

Datum opmeting: 2001-03-07

Schaal: 1/100



VLAAMS-
BRABANT