

Legende

gebouw

afsluiting, prikkeldraad

algemene afsluiting

afsluiting, betonpaaltjes + prikkeldraad

haag

beginpunt oeverbegroeiing

vaste bodem

slibbodem

The figure shows a cross-section profile of a ditch. The top part is a line drawing with a cyan line for 'vaste bodem' (firm ground) and a black line for 'slibbodem' (sludge bottom). A pink circle with a crosshair is labeled '705/111'. Red 'X' marks indicate 'afsluiting, prikkeldraad' (closure, barbed wire). Below the drawing is a table with four rows: BODEMPEIL, SLIBBODEM, CUMULAFSTAND, and TUSSENAFSTAND. The table has 16 columns corresponding to the profile segments.

BODEMPEIL	32.77	32.67	32.26	31.89	31.77	31.88	31.88	31.72	30.73	30.23	30.44	31.77	31.86	31.93	32.14	32.40	32.60	32.59	32.57
SLIBBODEM									30.73	30.37	30.51								
CUMULAFSTAND	-16.95	-13.80	-10.32	-6.93	-4.01	-2.03	-1.57	-1.10	-0.61	0.00	0.16	0.94	1.39	2.02	3.41	5.63	9.55	13.33	16.40
TUSSENAFSTAND	3.18	3.15	3.48	3.39	2.92	1.98	0.46	0.47	0.49	0.61	0.78	0.45	0.63	1.39	2.22	3.93	3.77	3.07	3.12

Gemeente Merchtem

B6037

Puttenbeek

VHAG: 705

Locatie ataspunt (LB72):

X-coördinaat: 138473,4988 Y-coördinaat: 181544,1373

DWARSPROFIELPLAN

Atlaspunt - 055

Datum opmeting: 1/08/2001

Schaal: 1/100

VLAAMS-BRABANT