

DWARSPROFIEL 19
 Schaal : 1/100
 Referentiehoogte : 0.00 mTAW

Samengestelde afstanden	4.02 3.96		3.90		3.88		3.88		3.88		3.88 3.86		3.79 4.44 4.44 4.41 4.41 4.46 4.46 4.46		3.04 3.01 3.01 1.96 1.75 1.61		1.45 1.54		1.55 1.67		1.78 1.88		2.02 2.20 2.41		3.38		4.37		4.64 4.72		4.63		4.51		4.53		4.56 4.51
Hoogte TAW	4.02 3.96		3.90		3.88		3.88		3.88		3.88 3.86		3.79 4.44 4.44 4.41 4.41 4.46 4.46 4.46		3.04 3.01 3.01 1.96 1.75 1.61		1.45 1.54		1.55 1.67		1.78 1.88		2.02 2.20 2.41		3.38		4.37		4.64 4.72		4.63		4.51		4.53		4.56 4.51
Hoogte TAW slib													2.01 1.87 0.01 0.26 0.76 1.67				1.38		1.70		1.95		2.08														
Tussenafstand	0.03	2.58		1.64		2.50		2.50		2.50	0.05	1.29	0.04 0.08 0.39 0.11 0.37 0.04	0.03 0.01 0.26 0.76	1.48	1.49	1.80	1.57	1.73	1.40	0.62 0.22 0.13	1.06	1.62		2.00	0.02	2.50		3.62		3.50		2.98	0.58			